

Ideal for Retrofit or New Construction Applications

Step 1 Choose your driver & light engine

Voltage	100-277V
Dimming	0-10V
CRI	>80
cUL	E485736
THD	>20%
PF	0.90
Max ambient	45°
Energy Star Rated	
IC Rated	



High efficiency driver and selected light engine.
Fits all reflector sizes.
Suitable for damp locations.

Step 2 Choose your Reflector
4", 6", 8", or 10"



Step 3 Optional New Construction Frame
4", 6", 8", or 10"



1

Light Engine and Driver (XX=CCT 3500K or 4000K)
CDL-18W-XXK (1,606 lm)
CDL-27W-XXK (2,342 lm)
CDL-40W-XXK (3,346 lm)



Stepdown transformer available for 347V applications (210041E)
Mounts directly to driver box.

2

Reflector Required - ordered separately
CDLR-4 (4 inch)
CDLR-6 (6 inch)
CDLR-8 (8 inch)
CDLR-10 (10 inch)



3

New Construction Frame Optional - ordered separately
CDLH-4 (4 inch)
CDLH-6 (6 inch)
CDLH-8 (8 inch)
CDLH-10 (10 inch)



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com