

Explosion-Proof High Bays





Certified Class 1, Div 2 (Groups A, B, C, D)

Suitable for hazardous environments where flammable gases, vapours, and liquids may exist. Also suited for wet locations, marine environments, and high vibration applications.







Round Explosion-Proof High Bay





PRODUCT #	WATTS	VOLTAGE	CCT	LUMENS	EFFICACY	COLOUR			
EXPR-60W-50K	60W	120-277V	5000K	8,870 lm	130 lm/W	Orange			
EXPR-100W-50K	100W	120-277V	5000K	15,967 lm	130 lm/W	Orange			
EXPR-150W-50K	150W	120-277V	5000K	23,834 lm	130 lm/W	Orange			
EXPR-WG-SM	Wire Guard for 60W EXPR Fixtures								
EXPR-WG-LG	Wire Guard for 100W/150W EXPR Fixtures								







EXPR-WG-SM



EXPR-100W-50K EXPR-150W-50K



EXPR-WG-LG

Linear Explosion-Proof High Bay





PRODUCT #	WATTS	VOLTAGE	CCT	LUMENS	EFFICACY	LENGTH		
EXPL-40W-2FT-50K	40W	120-277V	5000K	5,881 lm	130 lm/W	2 ft		
EXPL-80W-4FT-50K	80W	120-277V	5000K	11,202 lm	130 lm/W	4 ft		
EXPL-YK	Yoke Mount for EXPL Fixtures							
EXPL-WG-2FT	Wire Guard for 40W EXPL Fixtures							



EXPL-WG-4FT

EXPL-40W-2FT-50K



Wire Guard for 80W EXPL Fixtures

EXPL-WG-2FT



EXPL-80W-4FT-50K



EXPL-WG-4FT











View IES files and product sheets at www.csc-led.com Contact your local CSC LED representative for more information.