

Architectural Wall Pack 50W | 4000K | 347V



High-end style with super bright, energy efficient LEDs Ideal for building entrances, multi-use facilities, apartment buildings, institutions, schools, stairways and loading docks





TECHNICAL DATA



LIGHT SPECIFICATIONS

| Lumens | 5,193 lm |
|------------|------------|
| Efficacy | 104.5 lm/W |
| CCT | 4000K |
| CRI | 83.5 |
| Beam Angle | 90 x 120 |
| L70 Life | 50,000 hrs |
| Dimmable | No |
| Warranty | 10-year |


APPROVALS AND LISTINGS

| cUL | E482965 |
|-----|----------|
| DLC | PAS1D9W1 |

ILLUMINANCE AT A DISTANCE

| Illuminance at a Distance | | | | |
|----------------------------|----------------------|-------------------|--|--|
| | Center Beam fc | Beam Width | | |
| 17.0 R | 8.02 fc 🖌 | 29.9 ft 38.5 ft | | |
| 34.0ft | 2.00 fc | 59.8 ft 77.1 ft | | |
| 51.0R | 0.89 fc | 89.7 ft 115.6 ft | | |
| 68.0R | 0.50 fc | 119.6 ft 154.1 ft | | |
| 85.0R | 0.32 fc | 149.5 ft 192.7 ft | | |
| | 0.22 fc | 179.4 ft 231.2 ft | | |
| 102.0R Vert. Spread: 82.6° | | | | |
| | Horiz, Spread: 97.2° | | | |

DIMENSIONS




ELECTRICAL

| Wattage | 50W |
|----------------|-------------|
| Voltage | 347V |
| Power Factor | 0.91 |
| THD | 13.69% |
| Operating Temp | -40 to 40°C |

CONSTRUCTION

| Housing | Aluminum |
|------------|--------------------|
| Finish | Multi-coat, powder |
| Colour | White |
| IP Rating | IP65 |
| Weight | 4.5 lbs |
| Carton Qty | 4 |

ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com