

# corn lamps

CSCLED



LED replacement lamps for metal halide and high pressure sodium  
Ideal for use in high bays, area lights, flood lights, wall packs and more

Samsung LEDs • IP64 rated • 5-year warranty  
High efficiency • Long life (L70) 50,000 hours  
Ballast bypass type • Suitable for enclosed fixtures

4.5KV  
Surge  
Suppression

8-540 Jamieson Parkway, Cambridge, ON N3C 0G5  
519.880.9833 | orders@csc-led.com

121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8  
778.730.0448 | ordersbc@csc-led.com

[www.csc-led.com](http://www.csc-led.com)

# corn lamps

CSCLED

SIZING: Use 3:1 ratio  
to compare with new HID lamps  
or 4:1 when comparing to burned-in lamps

15W  
19W



Part Number	CLW-15WBCA1-50K	CLW-19WBCA1-50K
Power	15W	19W
Lumens	2,102 lm	2,500 lm
CRI	>80	>80
PFC	>0.90	>0.90
Base	E26	E26
Dimensions	Φ65*166 mm	Φ65*186 mm

Input Voltage	120-277V
CUL	E496280
Colour Temperature	5000K
Beam Angle	360°
Operating Temp	-40° to 45° C
Housing	PC and Aluminum
Cover	Clear

24W  
36W  
54W



Part Number	CLW-24WBCA1-50K	CLW-36WBCA1-50K	CLW-54WBCA1-P50K	CLW-54WBCA1-EP50K
Power	24W	36W	54W	54W
Lumens	3,242 lm	4,685 lm	7,089 lm	6,423 lm
CRI	>80	80	>80	80
PFC	>0.90	0.90	>0.90	0.90
Base	E26	E26	E26	E39
Dimensions	Φ65*196 mm	Φ87*242 mm	Φ87*254 mm	Φ87*272 mm

75W  
100W  
125W



Part Number	CLW-75WBCA1-M50K	CLW-75WBCA1-EM50K	CLW-100WBCA1-E50K	CLW-125WBCA1-E50K
Power	75W	75W	100W	125W
Lumens	9,929 lm	8,749 lm	12,569 lm	15,142 lm
CRI	>80	80	80	80
PFC	>0.90	0.90	0.90	0.90
Base	E26	E39	E39	E39
Dimensions	Φ87*291 mm	Φ87*309 mm	Φ130*289 mm	Φ130*314 mm