

CWP02 40W Wall Pack

CWP02 series Wall Packs Ideal for exterior security and entryway lighting





TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	5,740 lm
Efficacy	144.48 lm/W
CCT	5000K
CRI	80
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	PLGAIXCUYKQB

ILLUMINANCE AT A DISTANCE

	Illuminance at a Distance				
	Center Beam fc		Beam Width		
3.3R	110.9 fc 🔺	8.7 ft	7.3 ft		
6.6R	27.7 fc	17.4 ft	14.6 ft		
9.9R	12.3 fc	26.1 ft	21.9 ft		
13.2ft	6.9 fc	34.9 ft	29.2 ft		
16.5 R	4.4 fc	43.6 ft	36.5 ft		
19.8R	3.1 fc	52.3 ft	43.8 ft		
	Vert. Spread: 105.7° Horiz. Spread: 95.8°				

ISOCANDELA PLOT



ELECTRICAL

Wattage	40W
Voltage	120-277V
Power factor	0.90
THD	15%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum / Borosilicate glass
Colour	Bronze
IP rating	IP65
Weight	8.29 lbs
Carton qty	1

DIMENSIONS





Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com