

CWP03 120W Wall Pack

CWP03 Wall Packs

Ideal for security, warehouse, and entryway lighting



TECHNICAL DATA



LIGHT SPECIFICATIONS

| Lumens | 17,244 lm |
|----------|-------------|
| Efficacy | 142.75 lm/W |
| CCT | 4000K |
| CRI | 83 |
| Dimmable | 0-10V |
| Warranty | 10-year |


APPROVALS AND LISTINGS

| cUL | E482965 |
|-------------|--------------|
| DLC Premium | PL3IPN47I95E |

ILLUMINANCE AT A DISTANCE

| | Center Beam fc | Beam Width | |
|--------|--|------------|---------|
| 3.3ft | 348.0 fc 🧥 | 9.4 ft | 7.5 ft |
| 6.6R | 87.0 fc | 18.8 ft | 15.1 ft |
| 9.9ft | 38.7 fc | 28.2 ft | 22.6 ft |
| 13.2ft | 21.8 fc | 37.6 ft | 30.2 ft |
| 16.5ft | 13.9 fc | 47.0 ft | 37.7 ft |
| 19.8ft | 9.7 fc | 56.4 ft | 45.2 ft |
| | Vert. Spread: 109.9° Horiz. Spread: 97.6° | | |

ISOCANDELA PLOT




ELECTRICAL

| Wattage | 120W |
|----------------|--------------|
| Voltage | 120-277V |
| Power factor | 0.93 |
| THD | 8.68% |
| Operating temp | -40° to 40°C |

CONSTRUCTION

| Housing | Aluminum / Polycarbonate |
|------------|-----------------------------|
| Colour | Bronze |
| IP rating | IP65 |
| Weight | 7.54 lbs |
| Carton qty | 1 |

DIMENSIONS





Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

