

CWP03 60W Wall Pack, HV

CWP03 Wall Packs Ideal for security, warehouse, and entryway lighting

High impact polycarbonate optics Purpose-built for precision beam control LED driver inside and vandal resistance Heavy die-cast LM80 tested aluminum body Lumiled chips



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	8,146 lm
Efficacy	136.12 lm/W
CCT	4000K
CRI	83.7
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	PT92ID9P

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
Center Beam fc		Beam Width		
3.3ft	183.8 fc 📈	9.3 ft	7.9 ft	
6.68	46.0 fc	18.5 ft	15.8 ft	
9.9ft	20.4 fc	27.8 ft	23.7 ft	
13.2R	11.5 fc	37.1 ft	31.6 ft	
16.5R	7.4 fc	46.3 ft	39.5 ft	
19.8R	5.1 fc	55.6 ft	47.5 ft	
Vert. Spread: 109.1° Horiz. Spread: 100.3°				

ISOCANDELA PLOT




ELECTRICAL

Wattage	60W
Voltage	277-480V
Power factor	0.90
THD	15.02%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum / Polycarbonate
Colour	Bronze
IP rating	IP65
Weight	6.45 lbs
Carton qty	1

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com