

CWP03 60W Wall Pack



CWP03 Wall Packs Ideal for security, warehouse, and entryway lighting

High impact polycarbonate optics for precision beam control and vandal resistance

Purpose-built LED driver inside



LM80 tested

Lumiled chips

Heavy die-cast

aluminum body

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	8,756 lm
Efficacy	139.75 lm/W
CCT	4000K
CRI	83.1
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	PLQ2YC0JVNJ4

ILLUMINANCE AT A DISTANCE

enter Beam fc 189.4 fc 47.3 fc 21.0 fc	Beam Wid 9.2 ft 18.4 ft 27.6 ft	7.9 ft 7.9 ft 15.9 ft 23.8 ft
47.3 fc	18.4 ft	15.9 ft
21.0 fc	27.6 ft	23.8 f
11.8 fc	36.8 ft	31.7 ft
7.6 fc	46.0 ft	39.7 f
5.3 fc	55.2 ft	47.6 f
		5.3 fc 55.2 ft . Spread: 108.7°

ISOCANDELA PLOT




ELECTRICAL

Wattage	60W
Voltage	120-277V
Power factor	0.92
THD	13.03%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum / Polycarbonate
Colour	Bronze
IP rating	IP65
Weight	6 lbs
Carton qty	1

DIMENSIONS





Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com