

# 230W Flood / Area Light, 277-480V



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



Optional Field-Interchangable Mounting Arms (ordered separately)



Slip Fit FL01P-SF



Horizontal Arm FL01P-HA



Round Pole FL01P-RPA

## **TECHNICAL DATA**



#### LIGHT SPECIFICATIONS

Lumens	32,456
Efficacy	137.88 lm/W
CCT	5000K
Beam angle	90 x 120°
CRI	70
CRI Dimmable	70 0-10V


## **APPROVALS AND LISTINGS**

cUL	E482965

#### **ILLUMINANCE AT A DISTANCE**

	Center Beam fc	Beam Wi	dth
3.33M	87.8 fc	6.10 M	13.41 M
6.67M	22.0 fc	12.19 M	26.80 M
10.00M	9.76 fc	18.29 M	40.20 M
13.33M	5.49 fc	24.38 M	53.60 M
16.67M	3.51 fc	30.48 M	67.00 M
20.00M	2.44 fc	36.57 M	80.41 M

## **ISOCANDELA PLOT**




## **ELECTRICAL**

Wattage	230W
Voltage	277-480V
Power factor	0.90
THD	15%
Operating temp	-40° to 40°C

#### CONSTRUCTION

Housing	Aluminum
Finish	6mm, powder-coat
Colour	Bronze
IP rating	IP65
Weight	13.8 lbs
Carton qty	1

#### **DIMENSIONS**



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

