

240W Flood / Area Light, 277-480V



FL04 Series

Sleek, streamlined design with premium performance

LM80
Tested Chips

Polyester
Powder Coat Finish
Bronze Standard



Shown here with
Slip Fitter Mount

Highest Grade
Polycarbonate Optics

Type III Standard
Type V Available

Trunnion Mount Standard

Field-Interchangeable:
Slip Fitter, Pole, or Multi-Mount
Ordered Separately

Options available (ordered separately):

Pole Mount



FL04-PM

Multi Mount



FL04-MM

Slip Fit Mount



FL04-SF

Visor



FL04-SHIELD-LG

Photocell



FLPC-HV

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	31,053 lm
Efficacy	130.36 lm/W
CCT	4000K
CRI	72.9
L70 Life	54,000
Dimmable	0-10V
Warranty	10-year

APPROVALS AND LISTINGS


cUL	E482965
DLC	PL16V6ICQM0V

ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	26.5 fc	50.1 ft	118.1 ft
34.0ft	6.62 fc	100.3 ft	236.2 ft
51.0ft	2.94 fc	150.4 ft	354.4 ft
68.0ft	1.65 fc	200.6 ft	472.5 ft
85.0ft	1.06 fc	250.7 ft	590.6 ft
102.0ft	0.74 fc	300.8 ft	708.7 ft

■ Vert. Spread: 111.7°
 ■ Horiz. Spread: 147.9°

ISOCANDELA PLOT



ELECTRICAL

Wattage	240W
Voltage	277-480V
Power factor	0.93
THD	11.03%
Operating temp	-40 to 40°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Polyester powder coat
Colour	Bronze
IP rating	IP65
EPA rating	45° - 1.75 ft² Horizontal - 1.1 ft² Vertical - 2.3 ft²
Weight	15.87 lbs
Carton qty	1

DIMENSIONS

