

FL04B Flood / Area Light


200W | 3000K | 120-347V





TRUE UNIVERSAL POWER INPUT FROM 120-347V!

A versatile, clean, and modern appearance that brings a pleasing aesthetic to any project



Accessories (Ordered Separately):

Yoke Mount, Slip Fit, Pole Mount, Multi Mount, Motion Sensor Remote, Motion Sensor, Type IV and V Optics, Photocell and Recptacle













FL04-YK-LG

FL04-SF

FL04-PM

HB01R

HB01DMS-A



TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	24,215 lm
Efficacy	123 lm/W
CCT	3000K
CRI	70
L70 Life	50,000 hrs
Dimmable	0-10V
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLPPT6000SLI


DIMENSIONS (SHOWN WITH TRUNNION MOUNT)



ILLUMINANCE AT A DISTANCE



ISOCANDELA



ELECTRICAL

Wattage	200W	
Voltage	120-347V	
Power Factor	0.9	
THD	15%	
Operating Temp	-30 to 50°C	

CONSTRUCTION

Housing	Die-Cast Aluminum	
Cover	Polycarbonate	
Finish	Bronze	
IP Rating	IP65	
EPA	1.32 ft²	
Net Weight	5.97 kg	
Gross Weight	6.72 kg	
Carton Qty	1	
Carton Dimensions	Dimensions 690 x 380 x 155 mm	

ACCESSORIES (SOLD SEPARATELY)

Slip Fit	FL04-SF
Pole Mount	FL04-PM
Multi Mount	FL04-MM
Yoke Mount	FL04-YK-LG
Motion Sensor	HB01DMS-A
Motion Sensor Remote	HB01R
Photocell and Receptable for 120-277V sites	JL-200 and JL-205LV
Photocell and Receptable for 277-480V sites	JL-200 and JL-207E
Shield	FL04B-SHIELD-SM
Type IV Optics	FL04B-TYPE-IV
Type V Optics	FL04B-TYPE-V

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com