


# Mini Flood Light

Power Selectable | Colour Selectable | 120-277V

Ideal for landscaping, patio, and security lighting, signs, and building facades  
Excellent replacement for quartz halogen fixtures

**Die-Cast Aluminum Housing**  
with cooling fins for superior heat dissipation



**Power Selectable**  
(35W / 40W / 45W / 50W)

**Built-in Photocell**

**56 LED Chips**  
for even illumination

**0.5m Power Cord**

**High-Impact Polycarbonate Lens/Optics**



**Colour Selectable**  
3000K / 4000K / 5000K

**Complete With Yoke Mount**  
Knuckle mount sold separately



**Rugged Polyester Powder Coat Finish**  
(Bronze)

Optional Accessories:  
Knuckle Mount (FLM-KNS)

Suggested Substitutions:  
FLM-30W-3CCT-LV  
FLM-70W-3CCT-UD

## TECHNICAL DATA



### LIGHT SPECIFICATIONS


Lumens	6,312 lm
Efficacy	128.5 lm/W @ 4000K
CCT	3000K / 4000K / 5000K
CRI	70
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year

### APPROVALS AND LISTINGS


cUL	E482965
DLC	PLKQ5KQBZ3NB

### DIMENSIONS

Yoke Mount (Standard)



Knuckle Mount (Sold Separately)



### ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	9.32 fc	29.0 ft	53.8 ft
34.0ft	2.33 fc	58.0 ft	107.6 ft
51.0ft	1.04 fc	87.0 ft	161.4 ft
68.0ft	0.58 fc	116.0 ft	215.2 ft
85.0ft	0.37 fc	145.0 ft	269.0 ft
102.0ft	0.26 fc	174.0 ft	322.8 ft

■ Vert. Spread: 80.9°  
■ Horiz. Spread: 115.4°

### ELECTRICAL

Wattage	Selectable (35W/40W/45W/50W)
Voltage	120-277V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C


### CONSTRUCTION

Housing	Aluminum Alloy
Finish	Bronze
IP Rating	IP65
Fixture Weight	0.4 kg
Carton Weight	12.8 kg
Carton Qty	6
Carton Dimensions	468 x 326 x 284 mm

### ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM-KNS
Red Lens	FLM-50W-RED
Blue Lens	FLM-50W-BLU
Green Lens	FLM-50W-GRN

### ISOCANDELA



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | [ordersbc@csc-led.com](mailto:ordersbc@csc-led.com)