

200W High Bay, 277-480V



NEW HB7 series High Bay
Ideal for warehouses, factories, and workshops



TECHNICAL DATA





LIGHT SPECIFICATIONS

Lumens	27,610 lm
Efficacy	138.39 lm/W
CCT	5000K
CRI	80
L70 Life	60,000 hrs
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLM877MPKT3D

ILLUMINANCE AT A DISTANCE

C	enter Beam fc	Beam Wi	idth
17.0ft	33.2 fc	53.7 ft	53.1 ft
34.0ft	8.31 fc	107.3 ft	106.2 ft
51.0ft	3.69 fc	161.0 ft	159.3 ft
68,0R	2.08 fc	214.6 ft	212.4 ft
85.0ft	1.33 fc	268.3 ft	265.5 ft
102,0R	0.92 fc	321.9 ft	318.6 ft

ISOCANDELA PLOT




ELECTRICAL

Wattage	200W
Voltage	277-480V
Power factor	0.90
THD	15%
Operating temp	-30 to 50°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Black
IP rating	IP65
Weight	10.5 lbs
Carton qty	1
Carton weight	13.2 lbs
Carton dimensions	43.1 x 43.1 x 20.3 cm

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

