

200W High Bay, 120-277V



NEW HB7 series High Bay Ideal for warehouses, factories, and workshops



High grade aluminum body for superior heat dissipation

110° beam angle



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	27,506 lm
Efficacy	140.35 lm/W
CCT	5000K
CRI	80
L70 Life	60,000 hrs
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLPG2K02OF34

ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Wi	idth
17.0ft	32.9 fc	53.2 ft	52.7 ft
34.0ft -	8.23 fc	106.4 ft	105.3 ft
51.0ft -	3.66 fc	159.6 ft	158.0 ft
68.0R	2.06 fc	212.8 ft	210.7 ft
85.0R	1.32 fc	266.0 ft	263.3 ft
102.0R	0.91 fc	319.2 ft	316.0 ft

ISOCANDELA PLOT




ELECTRICAL

Wattage	200W
Voltage	120-277V
Power factor	0.90
THD	15%
Operating temp	-30 to 50°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Black
IP rating	IP65
Weight	10.5 lbs
Carton qty	1
Carton weight	13.2 lbs
Carton dimensions	43.1 x 43.1 x 20.3 cm

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitiam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com