

240W High Bay, 120-347V

HB7

NEW HB7 series High Bay
Ideal for warehouses, factories, and workshops



Long life, elevated driver
for cooler operation

2m power cord
0-10V dimmable

Polyester powder
coat finish (Black)

High grade aluminum body
for superior heat dissipation

110° beam angle

Shatter-proof
polycarbonate lens



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	31,153 lm
Efficacy	134.1 lm/W
CCT	5000K
CRI	80
L70 Life	50,000 hrs
Dimmable	0-10V
Warranty	5-year

APPROVALS AND LISTINGS


cUL	E482965
DLC Premium	PLI7PUXYH2BU

ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	37.1 fc	52.4 ft	52.9 ft
34.0ft	9.28 fc	104.9 ft	105.7 ft
51.0ft	4.12 fc	157.3 ft	158.6 ft
68.0ft	2.32 fc	209.8 ft	211.5 ft
85.0ft	1.48 fc	262.2 ft	264.3 ft
102.0ft	1.03 fc	314.7 ft	317.2 ft

■ Vert. Spread: 114.1°
■ Horiz. Spread: 114.5°

ISOCANDELA PLOT



ELECTRICAL

Wattage	240W
Voltage	120-347V
Power factor	0.90
THD	15%
Operating temp	-30 to 50°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Black
IP rating	IP65
Weight	10.3 lbs
Carton qty	1
Carton weight	13 lbs
Carton dimensions	42 x 42 x 20.5 cm

DIMENSIONS

