

High Bay

240W | 4000K | 120-347V



HB7B

HB7B series High Bay
Ideal for warehouses, factories, and workshops



Accessories (Ordered Separately):
Wire Guard, Motion Sensor, Motion Sensor Remote,
Yoke Mount, Aluminum or Polycarbonate Reflector,
Polycarbonate Bottom Cover, Frosted Lens



HB7B-AL-REF-LG



HB7B-PC-REF-LG



HB7B-YK-LG



HB7B-SENSOR



HB7B-REMOTE

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	36,387 lm
Efficacy	148 lm/W
CCT	4000K
CRI	80
Beam Angle	120°
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLDSUH5S95B9

ILLUMINANCE AT A DISTANCE



ISOCANDELA PLOT



ELECTRICAL

Wattage	240W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 55°C

CONSTRUCTION

Housing	Aluminum alloy
Cover	Clear glass
Finish	Black
IP Rating	IP65
Net Weight	5 kg
Carton Qty	1
Carton Weight	6.1 kg
Carton Dimensions	442 x 442 x 206 mm

ACCESSORIES (Ordered Separately)

Motion Sensor	HB7B-SENSOR
Motion Sensor Remote	HB7B-REMOTE
Yoke Mount	HB7B-YK-LG
Wire Guard	HB7B-WG-LG
Aluminum Reflector	HB7B-AL-REF-LG
Polycarbonate Reflector	HB7B-PC-REF-LG
PC Prism Cover	HB7B-PC-REF-LG-BCV
Frosted Lens	HB7B-FR-LENS-LG

Note: HB7B-SENSOR will dim the fixture to 10%, but will **not** turn the fixture fully off.

DIMENSIONS

