

High Bay 300W | 5000K | 120-277V





www.csc-led.com

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	45,215 lm
Efficacy	150 lm/W
ССТ	5000K
CRI	80
Beam Angle	120°
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLAFKW8P8B7P

ILLUMINANCE AT A DISTANCE

55.0 fc		52.3 R
13.8 fc	and the second second	
10.010	104.7 ft	104.6 ft
6.12 fc	157.1 ft	156.8 ft
3.44 fc	209.4 ft	209.1 ft
2.20 fc	261.8 ft	261.4 ft
1.53 fc	314.1 ft	313.7 R
	3.44 fc 2.20 fc 1.53 fc	3.44 fc 209.4 ft 2.20 fc 261.8 ft

ISOCANDELA PLOT



ELECTRICAL

Wattage	300W
Voltage	120-277V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C

CONSTRUCTION


Housing	Aluminum alloy
Cover	Tempered glass
Finish	Black
IP Rating	IP65
Net Weight	6.8 kg
Carton Qty	1
Carton Weight	8.5 kg
Carton Dimensions	442x 442 x 206 mm

ACCESSORIES (Ordered Separately)

Motion Sensor	HB7B-SENSOR
Motion Sensor Remote	HB7B-REMOTE
Yoke Mount	HB7B-YK-HG
Frosted Lens	HB7B-FR-LENS-HG
Wire Guard	HB7B-WG-HG

Note: HB7B-SENSOR will dim the fixture to 10%, but will **not** turn the fixture fully off.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com