

High Bay

100W | 5000K | 120-347V



HB7C

Ideal for warehouses, factories, gas stations, gymnasiums, grocery stores, and more



Instant Start and
0-10V Dimmable

Long Life, Elevated Driver
for cooler operation

2m Power Cord

Newly Designed,
Shatterproof
Polycarbonate Optics
meet/exceed DLC 5.1
glare standards

Easy Twist-on
Motion Sensor
Sold separately

Polyester Powder
Coat Finish
(Black)

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	14,398 lm
Efficacy	141 lm/W
CCT	5000K
CRI	80
Beam Angle	90°
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	5-year

APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLGXY9T3T720

ISOCANDELA PLOT



ILLUMINANCE AT A DISTANCE

Distance	Illuminance at a Distance	
	Center Beam fc	Beam Width
17.0ft	24.1 fc	35.1 ft 35.1 ft
34.0ft	6.02 fc	70.2 ft 70.1 ft
51.0ft	2.68 fc	105.3 ft 105.2 ft
68.0ft	1.51 fc	140.4 ft 140.2 ft
85.0ft	0.96 fc	175.5 ft 175.3 ft
102.0ft	0.67 fc	210.6 ft 210.3 ft

■ Vert. Spread: 91.8°
■ Horiz. Spread: 91.7°

ELECTRICAL

Wattage	100W
Voltage	120-347V
Surge Protection	4kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C

CONSTRUCTION

Housing	Die-Cast Aluminum
Lens	Polycarbonate
Finish	Powder coated
Finish Colour	Black
IP Rating	IP65
Net Weight	3 kg
Gross Weight	4 kg
Carton Qty	1
Carton Dimensions	382 x 382 x 196 mm

ACCESSORIES (Ordered Separately)

Motion Sensor	HB7B-SENSOR
Motion Sensor Remote	HB7B-REMOTE
Yoke Mount	HB7B-YK-SM
Wire Guard	HB7B-WG-SM
Aluminum Reflector	HB7B-AL-REF-SM
PC Reflector	HB7B-PC-REF-SM
PC Bottom Cover	HB7B-PC-REF-SM-BCV
Frosted Lens	HB7B-FR-LENS-SM

DIMENSIONAL DRAWINGS

