

LHB2 Linear High Bay 110W | 4000K | 120-347V



Ideal for warehouses, factories, workshops and more Energy efficient replacement for traditional fluorescent fixtures and HID high bays



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	15,311 lm
Efficacy	144.55 lm/W
CCT	4000K
CRI	80
L70 Life	170,000 hrs
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLVVOEM8Y3CX

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
	Center Beam fo	Beam Wi	dth	
17.0ft	20.7 fc	43.0 ft	41.2 ft	
34.0ft	5.17 fc	86.1 ft	82.4 ft	
51.0R	2.30 fc	129.1 ft	123.6 ft	
68.0ft	1.29 fc	172.1 ft	164.8 ft	
85.0R	0.83 fc	215.2 ft	206.0 ft	
102.0R	0.57 fc	258.2 ft	247.2 ft	
Vert. Spread: 103.4°				
	Horiz, Spread; 100,9°			

ISOCANDELA



ELECTRICAL

Wattage	110W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 80°C

CONSTRUCTION


Housing	Steel SGCC
Finish	White
IP Rating	IP20
Product Dimensions	630 x 300 x 48 mm
Ctn Qty	2
Carton Dimensions	720 x 360 x 185 mm

ACCESSORIES (Ordered Separately)

HB01DMS-B	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-110-165-WG	Wireguard
LHB-BRACKET-SM	Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-B) to function.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com