

LHB2 Linear High Bay

110W | 5000K | 120-347V



Ideal for warehouses, factories, workshops and more Energy efficient replacement for traditional fluorescent fixtures and HID high bays



Accessories (Ordered Separately):
Motion Sensor (HB01DMS-B), Motion Sensor Remote (HB01R),
Wireguard (LHB-110-165-WG), Bracket (LHB-BRACKET-SM)











TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	15,509 lm
Efficacy	145.7 lm/W
CCT	5000K
CRI	80
L70 Life	170,000 hrs
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLS9FLQVKR7P

ILLUMINANCE AT A DISTANCE



ISOCANDELA



ELECTRICAL

Wattage	110W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 80°C

CONSTRUCTION


Housing	Steel SGCC
Finish	White
IP Rating	IP20
Product Dimensions	630 x 300 x 48 mm
Ctn Qty	2
Carton Dimensions	720 x 360 x 185 mm

ACCESSORIES (Ordered Separately)

HB01DMS-B	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-110-165-WG	Wireguard
LHB-BRACKET-SM	Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-B) to function.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

