

LHB2 Linear High Bay 165W | 5000K | 120-347V



Ideal for warehouses, factories, workshops and more Energy efficient replacement for traditional fluorescent fixtures and HID high bays



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	23,364 lm
Efficacy	143 lm/W
ССТ	5000K
CRI	80
L70 Life	170,000 hrs
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLOY93KRLJHE

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance Center Beam fc Beam Width				
	Center Beam fc	Dealii Wi	uun	
17.0 R	31.1 fc 🧹	43.0 ft	41.3 ft	
10.000	7.79 fc	86.0 ft	82.7 ft	
34.0R				
51.0 R	3.46 fc	129.0 ft	124.0 ft	
	1.95 fc	172.0 ft	165.4 ft	
68.0R				
85.0 0	1.25 fc	215.0 ft	206.7 ft	
	0.87 fc	258.0 ft	248.1 ft	
102.0 R				
Vert. Spread: 103.3°				
Horiz. Spread: 101.1°				

ISOCANDELA



ELECTRICAL

Wattage	165W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 80°C

CONSTRUCTION


Housing	Steel SGCC
Finish	White
IP Rating	IP20
Product Dimensions	630 x 300 x 48 mm
Ctn Qty	2
Carton Dimensions	720 x 360 x 185 mm

ACCESSORIES (Ordered Separately)

HB01DMS-B	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-110-165-WG	Wireguard
LHB-BRACKET-SM	Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-B) to function.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com