

LHB2 Linear High Bay

300W | 4000K | 120-347V

Ideal for warehouses, factories, workshops and more Energy efficient replacement for traditional fluorescent fixtures and HID high bays



Accessories (Ordered Separately): Motion Sensor (HB01DMS-B), Motion Sensor Remote (HB01R), Wireguard (LHB-220-WG), Bracket (LHB-BRACKET-SM)









HB01DMS-B

I HB-300-WG

LHB-BRACKET-LG

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	43,063 lm
Efficacy	144.4 lm/W
CCT	4000K
CRI	80
L70 Life	170,000 hrs
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965

ILLUMINANCE AT A DISTANCE



ISOCANDELA



ELECTRICAL

Wattage	300W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 80°C

CONSTRUCTION


Housing	Steel SGCC
Finish	White
IP Rating	IP20
Product Dimensions	900 x 385 x 53 mm
Ctn Qty	1
Carton Dimensions	1000 x 460 x 125 mm

ACCESSORIES (Ordered Separately)

HB01DMS-B	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-300-WG	Wireguard
LHB-BRACKET-LG	Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-B) to function.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

