

LHB2 Linear High Bay 300W | 5000K | 120-347V



Ideal for warehouses, factories, workshops and more Energy efficient replacement for traditional fluorescent fixtures and HID high bays



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	43,547 lm	
Efficacy	145.6 lm/W	
CCT	5000K	
CRI	80	
L70 Life	170,000 hrs	
Warranty	5-year	


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLOWXZRU80IY

ILLUMINANCE AT A DISTANCE

	Illuminance at a l Center Beamfo	Distance Beam Wi	dth	
17.0ft	54.1 fc	53.3 ft	51.0 ft	
34.01	13.5 fc	106.5 ft	102.0 ft	
51.0R	6.01 fc	159.8 ft	152.9 ft	
68.0R	3.38 fc	213.1 ft	203.9 ft	
85.0R	2.16 fc	266.4 ft	254.9 ft	
102.0R	1.50 fc	319.6 ft	305.9 ft	
Vert. Spread: 114.9°				
Horiz, Spread: 112,6°				

ISOCANDELA



ELECTRICAL

Wattage	300W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 80°C

CONSTRUCTION


Housing	Steel SGCC
Finish	White
IP Rating	IP20
Product Dimensions	900 x 385 x 53 mm
Ctn Qty	1
Carton Dimensions	1000 x 460 x 125 mm

ACCESSORIES (Ordered Separately)

HB01DMS-B	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-300-WG	Wireguard
LHB-BRACKET-LG	Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-B) to function.

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com