

2'x 4' Backlit Panel



30W/40W/50W Selectable | Colour Tunable | 120-347V

High performance, light-weight luminaire suitable for lay-in, surface or pendant mounting
Ideal for use in schools, health care applications, offices, retail spaces, and more

120-347V, 0-10V
Dimmable Driver

Ultra-thin, Seamless
Aluminum Frame

Welded And Assembled
With Robotic Technology
for consistent quality control


Non-yellowing
Frosted Lens



Seismic Clips
Included

Waffle Stamping
increases heat dissipation
and driver life

Less than 2.2" Deep
ideal for tight plenum areas



CCT Tunable
(3500K / 4000K / 5000K)

Wattage Selectable
(30W / 40W / 50W)

Accessories (Sold Separately)

NOTE: OJ-626 is **required** for 347V applications



Luminaire Disconnect for 347V
OJ-626



Suspension Kit
PLB-SUSKIT



Surface Mount Kit
PLBX24-SK



Recessed Frame Kit
PLB24-RFK

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	5,235.3 lm @ 50W
Efficacy	111.37 lm/W
CCT	Tunable (35K/40K/50K)
CRI	83.8
Dimmable	0-10V
Beam Angle	120°
L70 Life	50,000 hrs
Warranty	7-year

APPROVALS AND LISTINGS

cUL	E491106
DLC	PL4LWTKEKRLE

ISOCANDELA PLOT



Note: Plotted @ 50W

ELECTRICAL

Wattage	Selectable (30W/40W/50W)
Voltage	120-347V
Power Factor	0.95
THD	13.4%
Operating Temp	-20 to 40°C

CONSTRUCTION

Housing	Metal
Finish	White
IP Rating	IP20
Product Dimensions	1209 x 602 x 55 mm
Carton Qty	2

ACCESSORIES (SOLD SEPARATELY)

PLBX24-SK	Surface Mount Kit
PLB24-RFK	Recessed Frame Kit
PLB-SUSKIT	Suspension Kit
OJ-626	Luminaire Disconnect for 347V

NOTE: OJ-626 is **required** for 347V applications

ILLUMINANCE AT A DISTANCE



Note: Plotted @ 50W