

PLBL Backlit Panel Light





Ideal for offices, gymnasiums, schools, hospitals, and more.



Optional Accessories (Sold Separately)

Surface Mount Kit (PLBL14-SK), Cable Kit (PLBL14/24-CABLE-KIT)



PLBL14-SK





TECHNICAL DATA





LIGHT SPECIFICATIONS

Lumens	4,410 lm
Efficacy	110.11 lm/W
CCT	4000K
CRI	82.4
Dimmable	0-10V
Life	50,000 hours
Warranty	7-year


APPROVALS AND LISTINGS

ETL	5000444
DLC	PLL6Y0HVYDTG

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance			
	Center Beam fc	Beam Wid	:h
4.0ft	92.5 fc	12.4 ft	12.3 ft
8.0 R	23.1 fc	24.8 ft	24.5 ft
12.0 R	10.3 fc	37.2 ft	36.8 ft
16.0R	5.8 fc	49.6 ft	49.0 ft
20.0 R	3.7 fc	62.0 ft	61.3 ft
■ Vert. Spread: 114.4° ■ Horiz. Spread: 113.7°			

DIMENSIONAL DRAWING



ELECTRICAL

Wattage	40W
Voltage	120-347V
Power Factor	0.92
THD	20.21 %
Operating temp	0° to 40°C

CONSTRUCTION


Housing	Aluminum
Finish	White
IP Rating	IP40 (Damp Location Rated)
Carton qty	4

ACCESSORIES (SOLD SEPARATELY)

Surface Mount Kit	PL14-SK
Cable Kit	PL14/24-CABLE-KIT



ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

