


PLBL Backlit Panel Light

40W | 5000K | 120-347V | 1'x4'

Ideal for offices, gymnasiums, schools, hospitals, and more.



Optional Accessories (Sold Separately)
Surface Mount Kit (PLBL14-SK), Cable Kit (PLBL14/24-CABLE-KIT)



PLBL14-SK



PLBL14/24-CABLE-KIT

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	4,544 lm
Efficacy	112.34 lm/W
CCT	5000K
CRI	83.7
Dimmable	0-10V
Life	50,000 hours
Warranty	7-year

APPROVALS AND LISTINGS

ETL	5000444
-----	---------


ELECTRICAL

Wattage	40W
Voltage	120-347V
Power Factor	0.92
THD	19.58 %
Operating temp	0° to 40°C

CONSTRUCTION


Housing	Aluminum
Finish	White
IP Rating	IP40 (Damp Location Rated)
Carton qty	4

ILLUMINANCE AT A DISTANCE




ACCESSORIES (SOLD SEPARATELY)


Surface Mount Kit	PL14-SK
Cable Kit	PL14/24-CABLE-KIT



DIMENSIONAL DRAWING



ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com