

PLBL Backlit Panel Light

40W | 3500K | 120-347V | 2'x2'

Ideal for offices, gymnasiums, schools, hospitals, and more.



Optional Accessories (Sold Separately)
Surface Mount Kit (PLBL22-SK), Cable Kit (PLBL22-CABLE-KIT)







TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	4,697 lm
Efficacy	114.06 lm/W
CCT	3500K
CRI	82.8
Dimmable	0-10V
Life	50,000 hours
Warranty	7-year


APPROVALS AND LISTINGS

ETL	5000444

ILLUMINANCE AT A DISTANCE



DIMENSIONAL DRAWING



ELECTRICAL

Wattage	40W
Voltage	120-347V
Power Factor	0.92
THD	21.4 %
Operating temp	0° to 40°C

CONSTRUCTION

Housing	Aluminum
Finish	White
IP Rating	IP40 (Damp Location Rated)
Carton qty	4


ACCESSORIES (SOLD SEPARATELY)

Surface Mount Kit	PL22-SK
Cable Kit	PL22-CABLE-KIT





ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

