

PLBL Backlit Panel Light

50W | 3500K | 120-347V | 2'x4'

Ideal for offices, gymnasiums, schools, hospitals, and more.



Optional Accessories (Sold Separately)
Surface Mount Kit (PLBL24-SK), Cable Kit (PLBL14/24-CABLE-KIT)







TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	4,908 lm
Efficacy	104.32 lm/W
CCT	3500K
CRI	83
Dimmable	0-10V
Life	50,000 hours
Warranty	7-year


APPROVALS AND LISTINGS

ETL	5000444

ILLUMINANCE AT A DISTANCE

	Illuminance at a Distance			
	Center Beam fc	Beam Widt	:h	
4.0ft	105.7 fc	12.3 ft	12.3 ft	
8.0 R	26.4 fc	24.6 ft	24.5 ft	
12.0ft	11.7 fc	37.0 ft	36.8 ft	
16.0R	6.6 fc	49.3 ft	49.0 ft	
20.0 R	4.2 fc	61.6 ft	61.3 ft	
■ Vert. Spread: 114.0° ■ Horiz. Spread: 113.7°				

DIMENSIONAL DRAWING



ELECTRICAL

Wattage	50W
Voltage	120-347V
Power Factor	0.91
THD	21.02 %
Operating temp	0° to 40°C

CONSTRUCTION

Housing	Aluminum
Finish	White
IP Rating	IP40 (Damp Location Rated)
Carton qty	4


ACCESSORIES (SOLD SEPARATELY)

Surface Mount Kit	PL24-SK
Cable Kit	PL14/24-CABLE-KIT





ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

