

Rotatable Wall Pack 80W | 4000K | 120-277V



Ideal for security lighting, wall washing, flood lighting, and more Use as a flood light - uplight, downlight, or both!





TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	10,598 lm
Efficacy	133.36 lm/W
CCT	4000K
Beam angle	60°
CRI	73.6
Dimmable	No
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC	PLGT401KNTJQ

ILLUMINANCE CONE



ELECTRICAL

Wattage	80W
Voltage	120-277V
Power factor	0.93
THD	12.32%
Operating temp	-30° to 45°C

CONSTRUCTION

Housing	Cast aluminum
Finish	Anodized finish
Colour	Black
IP Rating	IP65
Weight	6.68 lbs
Carton qty	2

ACCESSORIES (SOLD SEPARATELY)

RWP-EXT-PLATE Extension Plate



DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com