


# Solar Street / Area Light

40W | 5000K

Ideal for roadway lighting, parks, parking lots, farms, yards and marinas.




Optional Accessories: Solar Street Light mount (SSL-MNT), and remote (SSL-REMOTE)

TECHNICAL DATA


LIGHT SPECIFICATIONS

Lumens	8,000 lm
Efficacy	200 lm/W
CCT	5000K
CRI	>70
L70 Life	50,000 hrs
Warranty	3-year


LUMINOUS INTENSITY DISTRIBUTION CURVE



AVERAGE ILLUMINANCE EFFECTIVE FIGURE



SENSOR COVERAGE



ELECTRICAL

Wattage	40W
Operating temp	-20° to 60°C


CONSTRUCTION

Housing	Aluminum
Finish	Silver
Rating	IP66
EPA Rating (30° tilt)	2.28 ft²
Weight	26 lbs
Carton qty	1

Wattage	Battery Capacity	Full Power Run	Max Run Time	Charge Time	PV Panel Size
40W	307WHr	8 hrs	29 hrs	8.5 hrs	54W

- Notes:
- Full Power run time is based on a fully charged battery operating in Mode 1.
  - Max run time is based on a fully charged battery operating in Mode 3.
  - Charge time assumes direct sun exposure.

DIMENSIONS



3 PROGRAMMABLE PROFILES

- M1: 5H 100% brightness, then 5H 30% brightness and PIR (100% brightness maintained for 30 seconds after motion event), then 70% brightness to dawn
- M2: Output is constant at 70% to dawn
- M3: 30% brightness and PIR (100% brightness maintained for 30 seconds after motion event) to dawn

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | [ordersbc@csc-led.com](mailto:ordersbc@csc-led.com)