

Volumetric Troffer

40W | 3500K | 2x4



Suitable for use in commercial lighting areas, such as offices, retail spaces, hallways, and hospitality areas



Damp Location Rated

TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	5,066 lm
Efficacy	126.95 lm/W
CCT	3500K
CRI	82.9
L70 Life	50,000 hrs
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E491106
DLC Premium	PUOT2OCM

SPECTRAL POWER DISTRIBUTION



CHROMATICITY DIAGRAM



ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
Center Beam fc		Beam Width		
4.0ft	113.3 fc	10.0 ft	11.6 ft	
8.0R	28.3 fc	20.0 ft	23.2 ft	
12.0ft	12.6 fc	30.0 ft	34.8 ft	
16.0 R	7.1 fc	40.0 ft	46.4 ft	
20.0 R	4.5 fc	50.0 ft	58.0 ft	
■ Vert. Spread: 102.7° ■ Horiz. Spread: 110.8°				


ELECTRICAL

Wattage	40W
Voltage	100-347V
Power factor	0.88
THD	17.4 %
Operating temp	-20° to 40°C


CONSTRUCTION

Housing	Steel
Finish	White
IP Rating	IP40
Weight	22.2 lbs
Carton qty	12

ISOCANDELA PLOT



DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

