

CWP03 60W Wall Pack, HV

NEW CWP03 Wall Packs Ideal for security, warehouse, and entryway lighting High impact polycarbonate optics Purpose-built for precision beam control LED driver inside Heavy die-cast LM80 tested aluminum body Lumiled chips



www.csc-led.com

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	8,146 lm
Efficacy	136.12 lm/W
CCT	4000K
CRI	83.7
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PT92ID9P

ILLUMINANCE AT A DISTANCE

Illuminance at a Center Beam fc		Beam Width	
	Center beamint	Deant wit	iun -
3.3ft	183.8 fc 🔪	9.3 ft	7.9 ft
6.6R	46.0 fc	18.5 ft	15.8 ft
9.9ft	20,4 fc	27.8 ft	23.7 ft
	11.5 fc	37.1 ft	31.6 ft
13.2R	7.4 fc	46.3 ft	39.5 ft
16.5R		55.6 ft	
19.8R	5.1 fc	55.6 ft	47.5 ft
	Vert. Spread: 109.1°		

ISOCANDELA PLOT




ELECTRICAL

Wattage	60W
Voltage	277-480V
Power factor	0.90
THD	15.02%
Operating temp	-40° to 40°C

CONSTRUCTION

Housing	Aluminum / Polycarbonate
Colour	Bronze
IP rating	IP65
Weight	6.45 lbs
Carton qty	1

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com