

# 15W Flood Light



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



## TECHNICAL DATA




### LIGHT SPECIFICATIONS

Lumens	1,667
Efficacy	110.76 lm/W
CCT	5000K
Beam angle	90 x 120°
CRI	82.5
Dimmable	No
Rated hours	50,000
Warranty	10-year

### APPROVALS AND LISTINGS

cUL	E352127
DLC	PDG5SWUD

### DIMENSIONS



### ILLUMINANCE AT A DISTANCE

Distance	Illuminance at a Distance	
	Center Beam fc	Beam Width
17.0ft	1.91 fc	33.8 ft 50.6 ft
34.0ft	0.48 fc	67.7 ft 101.1 ft
51.0ft	0.21 fc	101.5 ft 151.7 ft
68.0ft	0.12 fc	135.3 ft 202.3 ft
85.0ft	0.08 fc	169.2 ft 252.8 ft
102.0ft	0.05 fc	203.0 ft 303.4 ft

■ Vert. Spread: 89.7°  
■ Horiz. Spread: 112.2°

### ELECTRICAL

Wattage	15W
Voltage	120-277V
Power factor	0.92
THD	19.67
Operating temp	-40° to 55°C

### CONSTRUCTION

Housing	Aluminum
Finish	6mm, powder coat
Colour	Matte black
IP rating	IP65
Weight	1.32 lbs
Carton qty	18

### NOTES

1m-cUL listed cable included

### PHOTOMETRIC SPECS

