

50W Flood Light



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	6,179
Efficacy	126.31 lm/W
CCT	4000K
Beam angle	90 x 120°
CRI	82.6
Dimmable	No
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E352127
DLC	PXATC8G6

DIMENSIONS



NOTES

1m-cUL listed cable included

Optional slip fitter adaptor: #Slipfit-UV



ELECTRICAL

Wattage	50W
Voltage	120-277V
Power factor	0.92
THD	16.54
Operating temp	-40° to 55°C

CONSTRUCTION

Housing	Aluminum
Finish	6mm, powder coat
Colour	Matte black
IP rating	IP65
Weight	3.96 lbs
Carton qty	6

ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	7.36 fc	32.7 ft	55.9 ft
34.0ft	1.84 fc	65.4 ft	111.8 ft
51.0ft	0.82 fc	98.1 ft	167.8 ft
68.0ft	0.46 fc	130.8 ft	223.7 ft
85.0ft	0.29 fc	163.5 ft	279.6 ft
102.0ft	0.20 fc	196.2 ft	335.5 ft

■ Vert. Spread: 87.8°
■ Horiz. Spread: 117.4°

PHOTOMETRIC SPECS

