

80W Flood Light



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	10,033
Efficacy	126 lm/W
CCT	4000K
Beam angle	90 x 120°
CRI	82.7
Dimmable	No
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E352127
DLC	PCXHNF4U

DIMENSIONS



ILLUMINANCE AT A DISTANCE

Distance (ft)	Illuminance at a Distance	
	Center Beam fc	Beam Width
17.0ft	11.00 fc	35.7 ft 62.4 ft
34.0ft	2.75 fc	71.4 ft 124.8 ft
51.0ft	1.22 fc	107.1 ft 187.2 ft
68.0ft	0.69 fc	142.7 ft 249.6 ft
85.0ft	0.44 fc	178.4 ft 312.0 ft
102.0ft	0.31 fc	214.1 ft 374.4 ft

■ Vert. Spread: 92.8°
■ Horiz. Spread: 122.8°

ELECTRICAL

Wattage	80W
Voltage	120-277V
Power factor	0.95
THD	16.02
Operating temp	-40° to 55°C

CONSTRUCTION


Housing	Aluminum
Finish	6mm, powder coat
Colour	Matte black
IP rating	IP65
Weight	15 lbs
Carton qty	1

NOTES

- 1m-cUL listed cable included
- Optional slip fitter adaptor: #Slipfit-UV



PHOTOMETRIC SPECS




Product # FL01-80W-40K-HA

WITH HORIZONTAL ARM



DIMENSIONS

Fixture



Horizontal Arm

