

230W Flood / Area Light



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination and more



Optional Field-Interchangable Mounting Arms (ordered separately)



Slip Fit FL01P-SF



Horizontal Arm FL01P-HA



Round Pole FL01P-RPA

TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	30,006
Efficacy	127.96 lm/W
CCT	5000K
Beam angle	90 x 120°
CRI	73
Dimmable	0-10V
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC	PLZXY4H1T42L

ILLUMINANCE AT A DISTANCE




ELECTRICAL

Wattage	230W
Voltage	120-277V
Power factor	0.93
THD	10.93%
Operating temp	-40° to 40°C


CONSTRUCTION

Housing	Aluminum
Finish	6mm, powder-coat
Colour	Bronze
IP rating	IP65
Weight	13.8 lbs
Carton qty	1

DIMENSIONS



ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

