

30W Streamline Flood Light

WITH KNUCKLE MOUNT



Ideal for landscape lighting, architectural flood lighting, and interior wall washing

Anodized aluminum body Slim, sleek and light weight LM80 tested LED chips Optical grade glass lens



Shown with round junction box

TECHNICAL DATA






LIGHT SPECIFICATIONS

Lumens	3,399 lm
Efficacy	119.86 lm/W
CCT	5,000K
Beam angle	110°
CRI	82.3
Rated hours	35,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC	PCERQW7P

DIMENSIONS





Unit: mm

Tolerance: ±1mm
A: 240 B: 165
C:66.8 D:29.5
E:38 F:16.5

ELECTRICAL

Wattage	30W
Voltage	120-277V
Power factor	0.89
THD	14.06%
Operating temp	-20° to 40°C

CONSTRUCTION

Housing	Die-cast aluminum
Finish	Powder coat
Colour	Bronze
IP rating	IP65
Weight	2.9 lbs
Carton qty	40

NOTES

Full colour box

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

