

300W Flood / Area Light



NEW FL04 Series

Sleek, streamlined design with premium performance

LM80
Tested Chips

Polyester
Powder Coat Finish
Bronze Standard

Shown here with
Slip Fitter Mount

Highest Grade
Polycarbonate Optics

Type III Standard
Type V Available

Trunnion Mount Standard

Field-Interchangeable:
Slip Fitter, Pole, or Multi-Mount
Ordered Separately

Options available (ordered separately):

Pole Mount



FL04-PM

Multi Mount



FL04-MM

Slip Fit Mount



FL04-SF

Motion Sensor or Photocell



FL04-MMS-KIT

FLPC-LV

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	38,665 lm
Efficacy	126.78 lm/W
CCT	4000K
CRI	70
L70 Life	54,000
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	PL7K2O8PPNVM

ILLUMINANCE AT A DISTANCE



ISOCANDELA PLOT



ELECTRICAL

Wattage	300W
Voltage	120-277V
Power factor	0.90
THD	15 %
Operating temp	-40 to 40°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Polyester powder coat
Colour	Bronze
IP rating	IP65
EPA rating	45° - 1.75 ft² Horizontal - 1.1 ft² Vertical - 2.3 ft²
Weight	17.64 lbs
Carton qty	1

DIMENSIONS

