

Product #

160W High Bay

HB5 series

Ideal for all indoor high bay applications including warehouses, manufacturing plants, showrooms, and retail applications



Fast easy installation with chain and hook suspension kit (1m) included



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	22,720 lm
Efficacy	143.62 lm/W
CCT	4000K
CRI	82.3
Beam angle	120°
Rated hours	50,000
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PYWF8SX2

ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Wi	dth
17.0ft -	26.9 fc	54.1 ft	55.0 ft
34.0ft -	6.7 fc	108.3 ft	110.0 ft
54.0R	3.0 fc	162.4 ft	165.1 ft
68.0ft	1.7 fc	216.6 ft	220.1 ft
85.0ft	1.1 fc	270.7 ft	275.1 ft
85.0R	0.7 fc	324.9 ft	330.1 ft
	Vert. Spread: 115.7°		

ISO CANDELA PLO




ELECTRICAL

Wattage	160W
Voltage	120-277V
Power factor	.96
THD	8.79 %
Operating temp	-20 to 40° C

CONSTRUCTION

Housing	Steel
Finish	Powder-coat
Colour	White
IP rating	IP54
Weight	23 lbs
Carton qty	1

DIMENSIONS





A:12.60" C: 1.97" B: 45.87" D: 3.78"

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com