

25W

ROTATABLE LUMINAIRE



Ideal for security lighting, wall washing, flood lighting, and more
Use as an uplight, downlight, or flood light

Rotatable
to offer flexible light control

Oversized Heat Sink
for superior thermal
management



Heavy Die Cast
Aluminum

Superior
anodized
paint finish



LM80 tested
CREE chips

Optional Extension Plate: RWP-EXT-PLATE
(ordered separately)

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	3,280 lm
Efficacy	129.66 lm/W
CCT	5000K
Beam angle	60°
CRI	73.5
Dimmable	No
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC PREMIUM	PL3VERZYMHTN

DIMENSIONS



**MAKE THE SMART CHOICE.
COMPARE LUMENS PER WATT
129+ LM/W**

ELECTRICAL

Wattage	25W
Voltage	100-277V
Power factor	0.91
THD	14.07%
Operating temp	-30° to 45° C

CONSTRUCTION

Housing	Cast aluminum
Finish	Anodized finish
Colour	Black
IP rating	IP65
Weight	4.07 lbs
Carton qty	4

ILLUMINANCE CONE

