

40W

**ROTATABLE LUMINAIRE**

Ideal for security lighting, wall washing, flood lighting, and more  
Use as an uplight, downlight, or flood light

Rotatable  
to offer flexible light control

Oversized Heat Sink  
for superior thermal  
management



Heavy Die Cast  
Aluminum

Superior  
anodized  
paint finish



Optional Extension Plate: RWP-EXT-PLATE  
(ordered separately)

LM80 tested  
CREE chips

## TECHNICAL DATA



## LIGHT SPECIFICATIONS

Lumens	5,131 lm
Efficacy	128.18 lm/W
CCT	5000K
Beam angle	60°
CRI	73.5
Dimmable	No
Rated hours	50,000
Warranty	10-year

## APPROVALS AND LISTINGS

cUL	E482965
DLC PREMIUM	PLFR1ZDBV8HU

## DIMENSIONS



MAKE THE SMART CHOICE.  
COMPARE LUMENS PER WATT  
**128+ LM/W**

## ELECTRICAL

Wattage	40W
Voltage	100-277V
Power factor	0.91
THD	18.95%
Operating temp	-30° to 45° C

## CONSTRUCTION

Housing	Cast aluminum
Finish	Anodized finish
Colour	Black
IP rating	IP65
Weight	4.29 lbs
Carton qty	4

## ILLUMINANCE CONE

