

30W Solar Street / Area Light

Ideal for roadway lighting, parks, parking lots, farms, yards and marinas 3 programmable working profiles



CSCLED


www.csc-led.com

TECHNICAL DATA


LIGHT SPECIFICATIONS

Lumens	6,000 lm
Efficacy	200 lm/W
CCT	5000K
CRI	>70
L70 Life	50,000 hrs
Warranty	3-year

LUMINOUS INTENSITY DISTRIBUTION CURVE



AVERAGE ILLUMINANCE EFFECTIVE FIGURE



Wattage	Battery Capacity	Full Power Run	Max Run	Charge time	PV Panel size
30W	230 WHr	8 hrs	29 hrs	8.5 hrs	42W

NOTES:

- Full Power Run time is based on a fully charged battery operating in Mode 1.

- Max run time is based on a fully charged battery operating in Mode 3 with a reasonable amount of motion events.

- Charge time assumes direct sun exposure.


ELECTRICAL

Wattage	30W
Operating temp	-20° to 60°C

CONSTRUCTION

Housing	Aluminum
Finish	Silver
IP rating	IP66
EPA rating (at 30° tilt)	1.88 ft ²
Weight	21.6 lbs
Carton qty	1

DIMENSIONS



3 PROGRAMMABLE PROFILES

M1: 5H 100% brightness, then 5H 30% brightness + PIR (100% brightness maintained for 30 seconds after motion event), then 70% brightness to dawn

M2: Output is constant at 70% to dawn

M3: 30% brightness + PIR (100% brightness maintained for 30 seconds after motion event) to dawn

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com