


# STOCK UP FOR FALL



## AL Architectural Linear Strip Lights

Direct (100% downlight) or Direct Indirect (70% downlight, 30% uplight) light dispersion

Customize your space with our 4 Backlit Connector options (sold separately)

Flexible mounting options sold separately (T-Bar, Recessed, Suspension, Wall Mounts)

**Wattage:** 40W or 80W

**Voltage:** 120-347V

**Colour Temperature:** 3000K/3500K/4000K

**Length:** 4 ft or 8 ft



## MWP03 Mini Wall Pack

Powerful performance in a compact, attractive package. Ideal for security lighting, commercial entrances, stairways, perimeter areas, and more

Built-in photocell can be bypassed with quick connect plug

DLC Premium

**Wattage:** 20W

**Voltage:** 120-277V

**Colour Temperature:** 4000K

## GL01 Grow Lights



Pictured: GL01-480W-FS-UD

Perfect for green house applications, cannabis and crop cultivation, vertical farming, and all other full spectrum grow light applications

IP65 rated for wet/damp locations

AC Parallel Connector Cable connects fixtures for daisy chain power configuration (sold separately)

**Wattage:** 480W or 660W

**Voltage:** 120-347V

**Full Spectrum**

## HB7C High Bays



Ideal for warehouses, factories, gas stations, gymnasiums, grocery stores, and more

Newly designed, shatterproof polycarbonate optics meet/exceed DLC 5.1 glare standards

A variety of compatible mounts and accessories available (sold separately)

**Wattage:** 100W or 300W

**Voltage:** 120-277V, 120-347V, or 277-480V

**Colour Temperature:** 4000K or 5000K



For more product information, including IES files, product sheets, and more, please visit [www.csc-led.com](http://www.csc-led.com) or scan the QR code with your smartphone!

