



EML Series

# EMERGENCY LIGHTING

Built for Safety, Performance, and Peace of Mind!

# RUNNING MAN SIGNS

COMBOS, EDGE-LIT,  
SELF-POWERED



## KEY FEATURES: 2 HEAD COMBOS

### Maintenance-Free Battery

Ni-Cd battery\*  
Lead Acid battery\*\*

### Push Button Test Switch

pilot LED for AC ON and CHARGE

### Up to 2 Hours Emergency Power Duration

as a standalone unit

### Universal Spider Knockout Pattern and Keyhole Slots

stamped into the cabinet back for easy installation

### 2 Adjustable Lamp Heads

### Multiple Conduit Entry Knockouts\*\*

\*EML-RMC-P-UD-SP    \*\*EML-RMC-S-UD-36W



## VERSATILE APPLICATIONS

With wall, ceiling, or flag mounting and single or double-sided options (all pictograms included), these signs fit any space. Built for safety with a UL-94V-0 flame rating and damp-location suitability, making them an excellent choice for virtually any application.

## EML Series

# RUNNING MAN SIGNS

Choose from self-powered and 6-24VDC models with ceiling, flag, or wall mounting options to suit any project!



EML-RMC-P-UD-SP



EML-RMC-S-UD-36W



EML-RMS-E-UDC  
EML-RMS-E-UD-SP



EML-RMS-P-UDC  
EML-RMS-P-UD-SP



EML-RMS-S-UDC  
EML-RMS-S-UD-SP



### Running Man Combos

Max discharge time for self-powered models is 120 minutes.

Fixtures	Sign Power	Lamp Power	Voltage	Style	Housing	Battery Type	Battery Capacity
EML-RMC-P-UD-SP	3W	1W x 2	120-347V	2 Head Combo	Thermoplastic	Ni-Cd	Self-Powered
EML-RMC-S-UD-36W	2W	2W x 2	120-347V	2 Head Combo	Steel	Lead Acid	36W

### Running Man Signs

Fixtures	Sign Power	Voltage	Style	Housing	Battery Type	Battery Capacity
EML-RMS-E-UDC	2W	120-347V/6-24VDC	Edge-Lit	Aluminum	N/A	N/A
EML-RMS-E-UD-SP	4W	120-347V	Edge-Lit	Aluminum	Ni-Cd	Self-Powered
EML-RMS-P-UDC	2W	120-347V/6-24VDC	Running Man	Thermoplastic	N/A	N/A
EML-RMS-P-UD-SP	3W	120-347V	Running Man	Thermoplastic	Ni-Cd	Self-Powered
EML-RMS-S-UDC	3W	120-347V/6-24VDC	Running Man	Steel	N/A	N/A
EML-RMS-S-UD-SP	4W	120-347V	Running Man	Steel	Ni-Cd	Self-Powered



For information on the complete series including IES files, spec sheets, and more, visit [www.csc-led.com](http://www.csc-led.com)

# EMERGENCY LIGHTING

BATTERY UNITS, REMOTE HEADS, DUAL HEAD



## KEY FEATURES: BATTERY UNITS

**Multiple Conduit Entry Knockouts**

**Universal Spider Knockout Pattern and Keyhole Slots**

stamped into the cabinet back for easy installation

**Push Button Test Switch**

pilot LED for AC ON and CHARGE

**Maintenance Free Battery**

**Short Circuit and Brown Out Protection**

## KEY FEATURES: REMOTE & DUAL HEADS

**Includes Standard Canopy**

allowing for mounting to electrical Junction Boxes

**Fire Resistant Thermoplastic Housing**

**Maintenance-Free Ni-Cd Battery\***

long-lasting battery and simple installation

**1 or 2 Adjustable Swivel Heads\*\***

**2 Adjustable Lamp Heads\***

**Operates from the Power & Control Circuitry of Emergency Lighting Battery Units and DC Power Back-Up Systems\*\***

\*Dual Head Only

\*\*Remote Heads Only



## COMPLETES ANY PROJECT

Complete your project with our full emergency lighting lineup — from self-powered Running Man signs and Battery Units to Remote Heads and a variety of housing options designed to keep every space safe, visible, and code-compliant.

# EMERGENCY LIGHTING

Complete your project with Battery Units, Remote Heads, and Dual Heads — delivering reliable emergency lighting that maximizes safety, performance, and peace of mind!



Battery Units



Remote Heads



Dual Head



## Battery Units

Max discharge time is 120 minutes for Battery Units and Dual Head.

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens	Battery Capacity
EML-BU-S-UD-36W	2W x 2	120-347V	Battery Unit	Steel	212 lm	36W
EML-BU-S-UD-72W	2W x 2	120/347V	Battery Unit	Steel	238 lm	72W
EML-BU-S-UD-140W	5W x 2	120/347V	Battery Unit	Steel	755 lm	140W

## Remote Heads

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens
EML-RH-P-DC-2W-1H	2W x 1	6-24V	1 x LED Head	Thermoplastic	125 lm
EML-RH-P-DC-5W-1H	5W x 1	6-24V	1 x LED Head	Thermoplastic	377 lm
EML-RH-P-DC-7W-1H	7W x 1	6-24V	1 x LED Head	Thermoplastic	410 lm
EML-RH-P-DC-4W-2H	2W x 2	6-24V	2 x LED Heads	Thermoplastic	212 lm
EML-RH-P-DC-10W-2H	5W x 2	6-24V	2 x LED Heads	Thermoplastic	755 lm
EML-RH-P-DC-14W-2H	7W x 2	6-24V	2 x LED Heads	Thermoplastic	804 lm

## Dual Head

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens	Battery Capacity
EML-DH-P-UD-SP	2W x 2	120-347V	Dual Head	Thermoplastic	260 lm	Self-Powered



For information on the complete series including IES files, spec sheets, and more, visit [www.csc-led.com](http://www.csc-led.com)

[www.csc-led.com](http://www.csc-led.com) | [info@csc-led.com](mailto:info@csc-led.com) | [cscledcorp](http://cscledcorp.com)





**BC BRANCH**

1140-2375 Fremont St  
Port Coquitlam, BC V3B 0N9  
(778) 730-0448

**AB BRANCH**

13-2355 52 Ave SE  
Calgary, AB T2C 4X7  
(403) 907-0212

**ON HEAD OFFICE**

8-540 Jamieson Pkwy  
Cambridge, ON N3C 0G5  
(519) 880-9833