



EML Series

EMERGENCY LIGHTING

Built for Safety, Performance, and Peace of Mind!

RUNNING MAN SIGNS

COMBOS, EDGE-LIT,
SELF-POWERED



KEY FEATURES: 2 HEAD COMBOS

Maintenance-Free Battery

Ni-Cd battery*
Lead Acid battery**

Push Button Test Switch

pilot LED for AC ON and CHARGE

Up to 2 Hours Emergency Power Duration

as a standalone unit

Universal Spider Knockout Pattern and Keyhole Slots

stamped into the cabinet
back for easy installation

2 Adjustable Lamp Heads

Multiple Conduit Entry Knockouts**

*EML-RMC-P-UD-SP **EML-RMC-S-UD-36W



VERSATILE APPLICATIONS

With wall, ceiling, or flag mounting and single or double-sided options (all pictograms included), these signs fit any space. Built for safety with a UL-94V-0 flame rating and damp-location suitability, making them an excellent choice for virtually any application.

EML Series

RUNNING MAN SIGNS

Choose from self-powered and 6-24VDC models with ceiling, flag, or wall mounting options to suit any project!



EML-RMC-P-UD-SP



EML-RMC-S-UD-36W



EML-RMS-E-UDC
EML-RMS-E-UD-SP



EML-RMS-P-UDC
EML-RMS-P-UD-SP



EML-RMS-S-UDC
EML-RMS-S-UD-SP



Running Man Combos

Max discharge time for self-powered models is 120 minutes.

Fixtures	Sign Power	Lamp Power	Voltage	Style	Housing	Battery Type	Battery Capacity
EML-RMC-P-UD-SP	3W	2W x 2	120-347V	2 Head Combo	Thermoplastic	Ni-Cd	Self-Powered
EML-RMC-S-UD-36W	2W	2W x 2	120-347V	2 Head Combo	Steel	Lead Acid	36W

Running Man Signs

Fixtures	Sign Power	Voltage	Style	Housing	Battery Type	Battery Capacity
EML-RMS-E-UDC	2W	120-347V/6-24VDC	Edge-Lit	Aluminum	N/A	N/A
EML-RMS-E-UD-SP	4W	120-347V	Edge-Lit	Aluminum	Ni-Cd	Self-Powered
EML-RMS-P-UDC	2W	120-347V/6-24VDC	Running Man	Thermoplastic	N/A	N/A
EML-RMS-P-UD-SP	3W	120-347V	Running Man	Thermoplastic	Ni-Cd	Self-Powered
EML-RMS-S-UDC	3W	120-347V/6-24VDC	Running Man	Steel	N/A	N/A
EML-RMS-S-UD-SP	4W	120-347V	Running Man	Steel	Ni-Cd	Self-Powered



For information on the complete series including IES files, spec sheets, and more, visit www.csc-led.com

www.csc-led.com | info@csc-led.com | [cscledcorp](http://cscledcorp.com)



EMERGENCY LIGHTING

BATTERY UNITS, REMOTE HEADS, DUAL HEAD



KEY FEATURES: BATTERY UNITS

Multiple Conduit Entry Knockouts

Universal Spider Knockout Pattern and Keyhole Slots

stamped into the cabinet back for easy installation

Push Button Test Switch

pilot LED for AC ON and CHARGE

Maintenance Free Battery

Short Circuit and Brown Out Protection

KEY FEATURES: REMOTE & DUAL HEADS

Includes Standard Canopy

allowing for mounting to electrical Junction Boxes

Fire Resistant Thermoplastic Housing

Maintainence-Free Ni-Cd Battery*

long-lasting battery and simple installation

1 or 2 Adjustable Swivel Heads**

2 Adjustable Lamp Heads*

Operates from the Power & Control Circuitry of Emergency Lighting Battery Units and DC Power Back-Up Systems**

*Dual Head Only

**Remote Heads Only



COMPLETES ANY PROJECT

Complete your project with our full emergency lighting lineup — from self-powered Running Man signs and Battery Units to Remote Heads and a variety of housing options designed to keep every space safe, visible, and code-compliant.

EML SERIES

EMERGENCY LIGHTING

Complete your project with Battery Units, Remote Heads, and Dual Heads — delivering reliable emergency lighting that maximizes safety, performance, and peace of mind!



Battery Units



Remote Heads



Dual Head



Battery Units

Max discharge time is 120 minutes for Battery Units and Dual Head.

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens	Battery Capacity
EML-BU-S-UD-36W	2W x 2	120-347V	Battery Unit	Steel	212 lm	36W
EML-BU-S-UD-72W	2W x 2	120/347V	Battery Unit	Steel	238 lm	72W
EML-BU-S-UD-140W	5W x 2	120/347V	Battery Unit	Steel	755 lm	140W

Remote Heads

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens
EML-RH-P-DC-2W-1H	2W x 1	6-24V	1 x LED Head	Thermoplastic	125 lm
EML-RH-P-DC-5W-1H	5W x 1	6-24V	1 x LED Head	Thermoplastic	377 lm
EML-RH-P-DC-7W-1H	7W x 1	6-24V	1 x LED Head	Thermoplastic	410 lm
EML-RH-P-DC-4W-2H	2W x 2	6-24V	2 x LED Heads	Thermoplastic	212 lm
EML-RH-P-DC-10W-2H	5W x 2	6-24V	2 x LED Heads	Thermoplastic	755 lm
EML-RH-P-DC-14W-2H	7W x 2	6-24V	2 x LED Heads	Thermoplastic	804 lm

Dual Head

Fixtures	Lamp Power	Voltage	Style	Housing	Lumens	Battery Capacity
EML-DH-P-UD-SP	2W x 2	120-347V	Dual Head	Thermoplastic	260 lm	Self-Powered



For information on the complete series including IES files, spec sheets, and more, visit www.csc-led.com

www.csc-led.com | info@csc-led.com | [cscledcorp](http://cscledcorp.com)





BC BRANCH

1140-2375 Fremont St
Port Coquitlam, BC V3B 0N9
(778) 730-0448

AB BRANCH

13-2355 52 Ave SE
Calgary, AB T2C 4X7
(403) 907-0212

ON HEAD OFFICE

8-540 Jamieson Pkwy
Cambridge, ON N3C 0G5
(519) 880-9833