



MWP04 Series

MINI WALL PACKS

Illuminate Your Outdoor Space

MWP04 MINI WALL PACKS



KEY FEATURES

Power Selectable
10W / 15W / 20W

3CCT Selectable
3000K / 4000K / 5000K

Wet Location Rated
IP65

**Low Glare, Frosted
Polycarbonate Lens**

Built-In Photocell

120-347V Universal Driver
0-10V dimming



DEPENDABLE PERFORMANCE

Ideal for landscaping, patio, security lighting, and building facades, a perfect replacement for quartz halogen fixtures. Featuring a built-in Photocell for dusk-to-dawn operation, with a **frosted low-glare polycarbonate lens**, **IP65-rated aluminum housing**, and cooling fins for durable, long-lasting performance.



Check out our
YouTube channel for
more information on
our products!

MWP04 MINI WALL PACK

The MWP04 Mini Wall Pack combines compact design with dependable performance. It provides efficient, low-glare illumination for entrances, walkways, stairwells, and perimeter lighting—making it a versatile solution for commercial and industrial applications. Available in black or bronze, the MWP04 is a smart, reliable solution built for lasting value.



MWP04 Mini Wall Packs

Fixtures	Wattage	CCT	Voltage	Lumens	Finish
MWP04-20W-3P-3CCT-UD-BK	10W / 15W / 20W	3000K / 4000K / 5000K	120-347V	1322-2749 lm	Black
MWP04-20W-3P-3CCT-UD-BZ	10W / 15W / 20W	3000K / 4000K / 5000K	120-347V	1322-2749 lm	Bronze

Lumen Output Tables

and Product Numbers

MWP04-20W-3P-3CCT-UD-BK			
	3000K	4000K	5000K
10W	1322 lm	1394 lm	1437 lm
15W	1898 lm	2023 lm	2058 lm
20W	2557 lm	2729 lm	2749 lm

MWP04-20W-3P-3CCT-UD-BZ			
	3000K	4000K	5000K
10W	1322 lm	1394 lm	1437 lm
15W	1898 lm	2023 lm	2058 lm
20W	2557 lm	2729 lm	2749 lm



For information on the
complete series including IES files,
spec sheets, and more, visit
www.csc-led.com

www.csc-led.com | info@csc-led.com | [cscledcorp](http://cscledcorp.com)





BC BRANCH

1140-2375 Fremont St
Port Coquitlam, BC V3B 0N9
(778) 730-0448

AB BRANCH

13-2355 52 Ave SE
Calgary, AB T2C 4X7
(403) 907-0212

ON HEAD OFFICE

8-540 Jamieson Pkwy
Cambridge, ON N3C 0G5
(519) 880-9833