



PLB - Backlit Panel Light

High performance, light-weight luminaire suitable for lay-in, surface, or pendant mounting
Ideal for use in schools, health care applications, offices, retail spaces, and more

120-347V, 0-10V
Dimmable Driver

Ultra-thin, Seamless
Aluminum Frame

Welded And Assembled
With Robotic Technology
for consistent quality control

Non-yellowing
Frosted Lens



Colour Tunable via Dip Switch
(3500K/4000K/5000K)

Wattage Selectable
via Dip Switch

Seismic Clips
Included

Less than 2.2" Deep
ideal for tight plenum areas

Waffle Stamping
increases heat dissipation
and driver life



Pictured: PLB24-50W-3CCT-WS-UD

Accessories (Sold Separately)



NOTE: 0J-626 is **required** for 347V applications

Luminaire Disconnect for 347V

Suspension Kit

Surface Mount Kit

Recessed Frame Kit



PLB - Backlit Panel Light

Suitable for lay-in, surface, or pendant mounting



PRODUCT #	WATTS	VOLTAGE	CCT	LUMENS
PLB14-40W-3CCT-WS-UD	25W, 30W, 40W	120-347V	3500K/4000K/5000K	4,521.3 lm
PLB22-40W-3CCT-WS-UD	25W, 30W, 40W	120-347V	3500K/4000K/5000K	4,372.7 lm
PLB24-50W-3CCT-WS-UD	30W, 40W, 50W	120-347V	3500K/4000K/5000K	5,235.3 lm

PLB14-RFK	Drywall Frame for 1'x 4' PLB Backlit Panels
PLB22-RFK	Drywall Frame for 2'x 2' PLB Backlit Panels
PLB24-RFK	Drywall Frame for 2'x 4' PLB Backlit Panels
PLBX14-SK	Surface Mount Kit for 1'x 4' PLB Backlit Panels
PLBX22-SK	Surface Mount Kit for 2'x 2' PLB Backlit Panels
PLBX24-SK	Surface Mount Kit for 2'x 4' PLB Backlit Panels
PLB-SUSKIT	Suspension Kit for PLB Backlit Panels
0J-626	Luminaire Disconnect for 347V Applications



PLB14-40W-3CCT-WS-UD



PLB22-40W-3CCT-WS-UD



PLB24-50W-3CCT-WS-UD