

Architectural Wall Pack 50W | 4000K | 120-277V

High-end style with super bright, energy efficient LEDs Ideal for building entrances, multi-use facilities, apartment buildings, institutions, schools, stairways and loading docks





TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	5,193 lm
Efficacy	104.5 lm/W
CCT	4000K
CRI	83.5
Beam Angle	90 x 120
L70 Life	50,000 hrs
Dimmable	No
Warranty	10-year

APPROVALS AND LISTINGS


cUL

E482965

ILLUMINANCE AT A DISTANCE

	Illuminance at a Distance			
	Center Beam fc	Beam Width		
17.0 0	8.02 fc 🔪	29.9 ft 38.5 ft		
34.0ft -	2.00 fc	59.8 ft 77.1 ft		
51.0R	0.89 fc	89.7 ft 115.6 ft		
68.0R	0.50 fc	119.6 ft 154.1 ft		
85.0ft -	0.32 fc	149.5 ft 192.7 ft		
102.0ft	0.22 fc	179.4 ft 231.2 ft		
	Vert. Spread: 82.6° Horiz. Spread: 97.2°			

DIMENSIONS




ELECTRICAL

Wattage	50W
Voltage	120-277V
Power Factor	0.91
THD	13.69%
Operating Temp	-40 to 40°C

CONSTRUCTION

Housing	Aluminum
Finish	Multi-coat, powder
Colour	White
IP Rating	IP65
Weight	4.5 lbs
Carton Qty	4

ISOCANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com