



AWP02-12W
 AWP02-30W
 AWP02-50W
 AWP02-80W
 AWP02-120W





Architectural Wall Pack Installation Instructions

IMPORTANT

- Read instructions carefully before attempting to install fixture. Retain instruction for future reference.
- Disconnect power before installing or servicing.
- This fixture must be wired in accordance with the National Electrical Code and applicable local codes and ordinances.
- All wiring should be performed by a qualified electrician.
- This fixture is for outdoor use and should not be used in areas with limited ventilation or high ambient temperatures.

INSTALLATION

1. Open the fixture a minimum 90 degrees. Loosen the 2 screws and take off the back plate.
2. Secure the back plate to junction box with screws.
 Use silicone glue to seal between the back plate and mounting surface.
 Note: The UP direction. See Fig 1.
3. Hang the fixture on the back plate. Connect wires into wiring terminal; white wire to “Neutral” terminal, black wire to “Live” terminal, green wire to “Ground” terminal; and fix them by screws. Connect the ground wire to the back plate. See Fig 2.
 Please mention the main specification as following before wiring. (See Table 1)
4. Close fixture and tighten the 2 screws. See Fig 3.
5. Adjust the fixture to a proper angle.
6. Loosen the screws after the installation.



| Model | Input Voltage | Input Current | Watt | Power Factor | Dimming | Table 1 |
|------------|---------------|---------------|------|--------------|--------------|---------|
| AWP02-12W | 100-277VAC | 0.15A | 12W | ≥0.9 | N/A | |
| AWP02-30W | 100-277VAC | 0.38A | 30W | ≥0.9 | N/A | |
| AWP02-50W | 100-277VAC | 0.52A | 50W | ≥0.9 | N/A | |
| AWP02-80W | 100-277VAC | 1.0A | 80W | ≥0.9 | 0-10V/PWM/VR | |
| AWP02-120W | 100-277VAC | 1.5A | 120W | ≥0.9 | 0-10V/PWM/VR | |