

# Ideal for Retrofit or New Construction Applications

**Step 1** Choose your driver & light engine

Voltage	100-277V
Dimming	0-10V
CRI	>80
cUL	E485736
THD	>20%
PF	0.90
Max ambient	45°
Energy Star Rated	
IC Rated	




High efficiency driver and selected light engine.  
Fits all reflector sizes.  
Suitable for damp locations.

**Step 2** Choose your Reflector  
4", 6", 8", or 10"



**Step 3** Optional New Construction Frame  
4", 6", 8", or 10"



1

Light Engine and Driver (XX=CCT 3500K or 4000K)
CDL-18W-XXK (1,606 lm)
CDL-27W-XXK (2,342 lm)
CDL-40W-XXK (3,346 lm)

2

Reflector Required - ordered separately
CDLR-4 (4 inch)
CDLR-6 (6 inch)
CDLR-8 (8 inch)
CDLR-10 (10 inch)

3

New Construction Frame Optional - ordered separately
CDLH-4 (4 inch)
CDLH-6 (6 inch)
CDLH-8 (8 inch)
CDLH-10 (10 inch)



Stepdown transformer available for 347V applications (210041E)  
Mounts directly to driver box.



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | [ordersbc@csc-led.com](mailto:ordersbc@csc-led.com)